

# FLOS

03.6814.3BA1V White/White

## Light Supply Wall-Washer Trim Dimmable

Designed by FLOS Architectural, 2017


LED - LED array - 33.2W - 1771lm - 3000K - CRI> 90 - Beam° 36



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	33.2
Source flux (lm)	3225
Lumen Output (lm)	1771

### Physical

Colour	White/White
Trim	No
Orientation	Fixed
Recessed depth (mm)	290
Net weight (kg)	1.01
IP internal	20
IP external	44

### Download

[Mounting instructions](#)  PDF

### Photometric Files


[LDT / IES](#)  ZIP

### Technical Drawings

[2D](#)  ZIP



## Schematic light drawing



Beam Angle: 36°

h(m)	E(lx)	D(m)
1	2092	0.74
2	523	1.48
3	232	2.22
4	131	2.95
5	84	3.69

Luminous flux Luminaire  
1771 lm (EXTREME CUT OFF)

### Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	51
Extreme cut off	No

### Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable 1-10V