

Light Tube Ø 30 Direct 1200 mm Dimmable 1-10V


Designed by Vincent Van Duysen



Diffused LED light module to be installed in The Infra-Structure.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	30

Physical

Color	Black
Orientation	Fixed
Length (in)	48.98
IP internal	20

Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)


Photometric Files

LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)

Schematic light drawing



Beam Angle: 150°		
h(m)	E(lx)	D(m)
1	509	7.40
2	127	14.80
3	57	22.19
4	32	29.59
5	20	36.99



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	150
Beam angle C90-270 (°)	106

Electrical

Insulation class	III
Forward voltage (V)	48
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

System turning fastening elements 0°-90° with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.