

FLOS

SA.2423.5A146 Gold

Linear Wall Rupture 3 m

Designed by Thierry Dreyfus, 2018



Soft technology wall-mounted, recessed luminaire. LED modules to emit lights with different colour temperature depending on décor. 120/277V power supply not included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Wall recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Power (W)	53
Source flux (lm)	3420

Physical

Color	Gold
Trim	No
Orientation	Fixed
Length (in)	118.12
Net weight (lb)	169.8
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700

Electrical

Driver	Remote excluded
Dimmable	Yes

Notes

For personal configuration ask sales team.

Accessories & Power Supply



REQUIRED
Power supply

LEDSB96W24V-10V-D01
LED power supply source for
remote installation, 0-10V
Dimmable 24V/96W, 120-277V

REQUIRED
Power supply

LED96W24V-DMX-W01
LED power supply source for
remote installation, 0-10V
Dimmable 24V/96W, 120-277V