

Live End Feed

NEW

Designed by FLOS Architectural, 2024




Track

Feed unit for remote power supply unit. Power cable inserting is possible both from the Rear and the side.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light sources included | No                  |

Physical

|                 |       |
|-----------------|-------|
| Colour          | Black |
| Field cuttable  | No    |
| Net weight (kg) | 0.2   |
| IP internal     | 20    |

Download

Mounting instructions

PDF



Photometric

Extreme cut off                      No

Electrical


|                     |                                                     |
|---------------------|-----------------------------------------------------|
| Insulation class    | III                                                 |
| Forward voltage (V) | 24                                                  |
| Power supply        | Remote                                              |
| Dimmable            | Yes                                                 |
| Power supply type   | Non Dimmable,<br>Dimmable DALI 2,<br>Dimmable 1-10V |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not<br>Included)         |
| Batteries inside    | No                                                  |

Accessories & Power Supply



REQUIRED  
Power supply  
Electrical

60.9352  
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.




REQUIRED  
Power supply  
Electrical

60.9705  
Remote Power Supply Non Dimmable 24V. 60W. 220/240V



REQUIRED  
Power supply  
Electrical

60.9777A  
Remote Power Supply Non Dimmable 24V. 120W. 220/240V



REQUIRED  
Power supply  
Electrical

08.0613.14A  
Dimmable control box 1-10V, 24/48V. For remote installation.