



Luce Sferica S1

Designed by Ronan Bouroullec, 2025




110W - 5345lm - 2700K - CRI> 95

Modular suspension lamp emitting diffused light. Horizontal body in polished extruded aluminium with two LED strips for upward and downward emission. Integrated touch dimmer enables independent control of light outputs. Body encased in a sequence of hand-blown transparent glass spheres separated by traditional spacers. Can be installed in multiple parallel rows.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607075685
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	110
Lumen Output (lm)	5345

Physical

Colour	Glass
Length (mm)	1656
Cord length (mm)	2700
Canopy length/diameter (mm)	900
Canopy width (mm)	61
Canopy height (mm)	78
Net weight (kg)	10.35
Package volume (m3)	0.46
IP internal	20

Download

Mounting instructions



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

https://professional.flos.com/en/global/product/luce-sferica-s1-f3752000/

F3752000

Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
LED current (mA)	500
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmer on board

