

FLOS

06.5117.40 White

Mechanical Rod Rose Ø 140 mm

Designed by Vincent Van Duysen, 2017



Mechanical rod rose ø140 mm. Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|-----------------|---------------------|
| Mounting | Ceiling surface |
| Environments | Indoor dry location |
| Icos | No |
| Number of heads | 1 |

Physical

| | |
|-----------------|-------|
| Colour | White |
| Trim | No |
| Length (mm) | 400 |
| Net weight (kg) | 0.89 |
| IP internal | 20 |



Download

[Mounting instructions](#)

[↓ PDF](#)



Electrical

Emergency type No

Notes

The closure terminals will also be electrified and must be ordered separately.
Mechanic rod with a Ø50 connection rose: to fasten profiles. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Component

06.5135.14A

End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5135.40A

End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.14A

End Cap On board dimmer/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.40A

End Cap On board dimmer/FLOS
Control® by Casambi compatible