

## Mechanical Rod Rose Ø 50 mm

Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light sources included | no                  |
| Number of lamps        | 1                   |

### Physical

|             |       |
|-------------|-------|
| Color       | Black |
| Trim        | No    |
| Length (in) | 11.81 |
| IP internal | 20    |
| IP external | 20    |



### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Electrical

|                |    |
|----------------|----|
| Emergency type | No |
|----------------|----|

### Notes

The closure terminals will also be electrified and must be ordered separately.  
Mechanic rod with a Ø50 connection rose: to fasten profiles. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED  
Component

06.5135.14A  
End Cap Dali/1-10V/FLOS  
Control® by Casambi compatible



REQUIRED  
Component

06.5135.40A  
End Cap Dali/1-10V/FLOS  
Control® by Casambi compatible



REQUIRED  
Component

06.5142.14A  
End Cap On board dimmer/FLOS  
Control® by Casambi compatible



REQUIRED  
Component

06.5142.40A  
End Cap On board dimmer/FLOS  
Control® by Casambi compatible