

FLOS

06.5111.40 White

Mechanical Rod Rose Ø 50 mm

Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Icos	No
Number of heads	1

Physical

Colour	White
Trim	No
Length (mm)	300
Net weight (kg)	0.55
IP internal	20
IP external	20



Download

[Mounting instructions](#)



Electrical

Emergency type No

Notes

The closure terminals will also be electrified and must be ordered separately.
Mechanic rod with a Ø50 connection rose: to fasten profiles. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Component

06.5135.14A

End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5135.40A

End Cap Dali/1-10V/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.14A

End Cap On board dimmer/FLOS
Control® by Casambi compatible



REQUIRED
Component

06.5142.40A

End Cap On board dimmer/FLOS
Control® by Casambi compatible