

Mechanical Rod Rose Ø 50 mm

Designed by Vincent Van Duysen, 2017



Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no
Number of lamps	1

Physical

Color	White
Trim	No
Length (in)	15.75
IP internal	20
IP external	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF

Electrical

Emergency type	No
----------------	----

Notes

The closure terminals will also be electrified and must be ordered separately.
Mechanic rod with a Ø50 connection rose: to fasten profiles. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED Component	REQUIRED Component	REQUIRED Component	REQUIRED Component
06.5135.14A	06.5135.40A	06.5142.14A	06.5142.40A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible	End Cap Dali/1-10V/FLOS Control® by Casambi compatible	End Cap On board dimmer/FLOS Control® by Casambi compatible	End Cap On board dimmer/FLOS Control® by Casambi compatible