

FLOS

03.6260.14.CB Black

Mini Glo-Ball Casambi integrated NEW


Designed by FLOS Architectural, 2020



General lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 7 |
| System power (W) | 7.3 |
| Source flux (lm) | 715 |
| Lumen Output (lm) | 446 |
| Efficacy (lm/W) | 61.1 |

Physical

| | |
|-----------------|-------|
| Colour | Black |
| Trim | No |
| Orientation | Fixed |
| Length (mm) | 130 |
| Net weight (kg) | 0.45 |
| IP internal | 20 |
| IP external | 20 |

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric

| | |
|--------------------------|----------------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 80 |
| McAdam steps (SDCM) | 3 |
| LED Life / Failure Ratio | L80B50 > 50.000h (Tc=85°C) |

Electrical

| | |
|---------------------|------------------|
| Insulation class | III |
| Forward voltage (V) | 24 |
| Power supply | Remote excluded |
| Dimmable | Yes |
| Power supply type | Dimmable Casambi |
| Dimming range (%) | 1-100 |

Notes

Maximum 21 spots for a single driver. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.