


# FLOS

03.6305.14CDD Black


## Multi Spot 4 Dali Version

Designed by FLOS Architectural, 2016



LED - Power LED - 10W - 630lm - 2700K - CRI> 90 - Beam° 11

4 accent Spot LED module can be rapidly exchanged and repositioned without tools. Light elements are quick to position and connect automatically with magnets. Built-in dimming knob dims fixture (from 20-100%), DALI and 0-10V (from 10-100%). Standard beam spread is 14° additional interchangeable lenses available in 20° and 30°, and elliptical beam spread.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Power (W)              | 10                  |
| System power (W)       | 11.3                |
| Source flux (lm)       | 878                 |
| System flux (lm)       | 630                 |
| Efficacy (lm/W)        | 55.75               |

### Physical

|                 |       |
|-----------------|-------|
| Color           | Black |
| Orientation     | Fixed |
| Length (in)     | 4.7   |
| Net weight (lb) | 0.77  |
| IP internal     | 20    |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                          |                          |
|--------------------------|--------------------------|
| Lighting type            | Direct                   |
| Light distribution       | Symmetric                |
| CCT (K)                  | 2700                     |
| CRI>                     | 90                       |
| McAdam steps (SDCM)      | 3                        |
| LED Life / Failure Ratio | L80B50>50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 11                       |
| Beam angle C90-270 (°)   | 11                       |
| UGR <sub>L</sub>         | <10                      |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| Driver              | Remote excluded                       |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable DALI 2                       |
| Dimming range (%)   | 10-100                                |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Accessories & Power Supply



OPTIONAL  
Accessory  
Optical

08.8759.00

Elliptical lens



OPTIONAL  
Accessory  
Optical

08.8760.00

Frosted Medium lens



OPTIONAL  
Accessory  
Optical

08.8761.00

Frosted Flood lens