

FLOS

05.2967.C5 White

My Circuit Light Shadow Spot Ø45


Designed by Michael Anastassiades, FLOS Architectural, 2023



LED lighting module for installation in the My Circuit system. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product. Casambi version for wireless control.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
System power (W)	8
Source flux (lm)	844
Lumen Output (lm)	682

Physical

Colour	White
Orientation	Adjustable
Rotation (°)	360
Transversal tilting (°)	90
Length (mm)	159
Net weight (kg)	0.36
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

Schematic light drawing



Beam Angle:	31°		
h(m)	E(lx)	D(m)	
1	2424	0.56	
2	606	1.11	
3	269	1.67	
4	152	2.22	
5	97	2.78	

Luminous flux Luminaire
682 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Rf fidelity index	91
Rg gamut index	100
LED Life / Failure Ratio	L70B50>45.000h_Tc85°C
Beam angle C0-180 (°)	31
Beam angle C90-270 (°)	31
Extreme cut off	Yes
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	200
Power supply	Remote excluded
Dimmable	No
Power supply type	Non Dimmable

Notes

Ask us about bespoke track connector arm lengths.