



#### **My Circuit Lines**

Designed by Michael Anastassiades, 2023

2 x 23W - 2 x 1460lm - 3000K - CRI> 90 - Beam<sup>o</sup> 110

My Circuit Lines is a suspended lamp with diffused light composed of two vertical bars that can be oriented, attached to a spherical adapter with matte white finish compatible with My Circuit track system. Each element is made of extruded anodized aluminium with a White matte finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 90). Usable power cable length 300cm with adjustable brightness 10–100%.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

# 

#### Main specifications

Mounting	Track	
Environments	Indoor dry location	
Light source type	LED	
Light sources included	Yes	
LED type	Top LED	
Number of lamps	2	
Power (W)	23	
Source flux (lm)	2470	
Lumen Output (lm)	1460	

#### Physical

Colour	White	
Net weight (kg)	0.12	
IP internal	20	

#### Download

Mounting instructions

**业** PDF

#### Photometric Files

LDT / IES

₹ ZIP

#### **Technical Drawings**

2D <u>♣</u> ZIP 3D <u>♣</u> ZIP

## CE







### Ecodesign and Energy Labelling








Replaceable control gear by a professional

https://professional.flos.com/en/global/product/my-circuit-lines-05.2993.c5/

05.2993.C5

#### Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	296	3.01
2	74	6.03
3	33	9.04
4	19	12.06
5	12	15.07

Luminous flux luminaire 1460 lm Each line

#### Photometric

Light distribution	Asymmetric	
CCT (K)	3000	
CRI>	90	
McAdam steps (SDCM)	3	
Rf fidelity index	92	
Rg gamut index	100	
LED Life / Failure Ratio	L70B50>65000h (Tc=85°C)	
Beam angle C0-180 (°)	110	
Beam angle C90-270 (°)	110	
Extreme cut off	No	

#### Electrical

Insulation class	III	
Forward voltage (V)	48	
Power supply	Remote excluded	
Dimmable	Yes	
Power supply type	Dimmable Casambi	
Dimming range (%)	1-100	