



My Circuit Lines

Designed by Michael Anastassiades, 2023

2 x 23W - 2 x 1460lm - 3000K - CRI> 90 - Beam^o 110

My Circuit Lines is a suspended lamp with diffused light composed of two vertical bars that can be oriented, attached to a spherical adapter with matte white finish compatible with My Circuit track system. Each element is made of extruded anodized aluminium with a White matte finish and a diffuser in platinum optical silicone with an integrated LED strip (CRI 90). Usable power cable length 118 7/ DD"with adjustable brightness 10–100%.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mouriting	ITACK
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	2
Power (W)	23
Source flux (lm)	2470
System flux (lm)	1460

Physical

Color	White
Net weight (lb)	0.26
IP internal	20

Download

amily spec sheet	<u>↓</u> ZIP
ounting instructions	.↓. PDF

Photometric Files

LDT / IES



Technical Drawings

2D	业 ZIP
3D	⊥ ZIP










https://professional.flos.com/en-US/us/product/my-circuit-lines-05.2993.c5/

05.2993.C5

Schematic light drawing



E	Beam	Angle:	110
ŀ	(m)	E(lx)	D(n
1		296	3.01
2	2	74	6.03
3	3	33	9.04
_	ı	19	12.06
-	<u> </u>	12	15.0

Ecodesign and Energy Labelling





Non-replaceable light source



Replaceable control gear by a professional

Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	92
Rg gamut index	100
LED Life / Failure Ratio	L70B50>65000h (Tc=85°C)
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	48
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming range (%)	1-100