

FLOS

F1903009 Matte White

My Disc

Designed by Michael Anastassiades, 2023



42W - 2194lm - 2700K - CRI > 90

My Circuit Disc is a suspended lamp with diffused light composed of a slender horizontal disc crossed by a vertical stem with a refined balance of geometries. Matte white painted aluminum body with polycarbonate stem. Silk screened PMMA diffuser. Edge Lighting technology light source (CRI 95 90) and adjustable brightness 10–100%. Usable power cable length 300 cm to be connected to a canopy with matte white finish. Canopy has to be ordered separately, the electronics integrated in the canopy enable use of dimming systems: PUSH dimming, 1-10V, DALI.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Download

Mounting instructions



Photometric Files

LDT / IES



Main specifications

EAN	8059607057032
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	42
System flux (lm)	2194

Physical

Color	Matte White
Length (in)	23.62
Canopy dimension (mm)	71
Canopy width (in)	5.866
Net weight (lb)	10.04
Package height (in)	11.81
Package width (in)	27.36
Package length (in)	27.36
Package volume (in)	8842.86
IP internal	20

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Non-replaceable light source



<https://professional.flos.com/en-US/us/product/my-disc-f1903009/>


F1903009

©2022 Flos - P.IVA 00290820174 - 4/23/2024

professional.flos.com | info@flos.com 1/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Beam Angle: 110°

h(m)	E(lx)	D(m)
1	805	2.87
2	201	5.73
3	89	8.60
4	50	11.46
5	32	14.33

Luminous flux Luminaire
2194 lm

Photometric

Light distribution	Roto symmetric
CCT (K)	2700
CRI>	90

Electrical

Insulation class	I
Main voltage (Vac)	48
Forward voltage (V)	48
Driver	Remote excluded
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Accessories & Power Supply



REQUIRED

F1908009

My Disc Rose