

# FLOS

03.2215.14A Black

**Nano Spot** NEW

Designed by FLOS Architectural, 2020




LED - Power LED - 2W - 77lm - 2700K - CRI> 90 - Beam° 32

Accent lighting LED module to be installed in The Micro Running Magnet System.  
Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



## Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	2
System power (W)	2
Source flux (lm)	165
Lumen Output (lm)	77
Efficacy (lm/W)	48.13

## Physical

Colour	Black
Orientation	Adjustable
Rotation (°)	267
Longitudinal tilting (°)	90
Spot diameter (mm)	13
Length (mm)	41
Net weight (kg)	0.03
IP internal	20

## Download

Mounting instructions [↓ PDF](#)

## Photometric Files

LDT / IES [↓ ZIP](#)

## Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)


[Bim](#) [↓ ZIP](#)



## Ecodesign and Energy Labelling



## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
UGR <sub>L</sub>	<16

### Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)