

FLOS

09.8300.DV Glossy Sage

Oblique NEW

Designed by Vincent Van Duysen, 2020




LED - Top LED - 8W - 479lm - 2700K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Driver input: 24 V

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Table |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Top LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 8 |
| System power (W) | 18 |
| Source flux (lm) | 754 |
| System flux (lm) | 479 |

Physical

| | |
|-----------------|-------------|
| Colour | Glossy Sage |
| Orientation | Fixed |
| Net weight (kg) | 0.75 |
| IP internal | 20 |
| IP external | 20 |

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



| | | |
|-------------|-------|-------|
| Beam Angle: | 35° | |
| h(m) | E(lx) | D(m) |
| 1 | 229 | 2.18 |
| 2 | 57 | 4.36 |
| 3 | 25 | 6.54 |
| 4 | 14 | 8.72 |
| 5 | 9 | 10.90 |

Luminous flux Luminaire
479 lm

Photometric

| | |
|--------------------------|-------------------------------|
| Lighting type | Direct |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| LED Life / Failure Ratio | L90B10 > 50.000h (Tc=85°C) |
| Beam angle C0-180 (°) | 35 |
| Beam angle C90-270 (°) | 46 |

Electrical

| | |
|---------------------------|-----------------|
| Insulation class | III |
| Power supply | Remote included |
| Dimmable | Yes |
| Power supply type | Dimmable |
| Emergency | No |
| Induction recharge QI | No |
| Charging socket/connector | USB-C |