

FLOS

09.8300.DX Matte Rust

Oblique NEW

Designed by Vincent Van Duysen, 2020




LED - Top LED - 8W - 479lm - 2700K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------|---------------------|
| Mounting | Table |
| Environment | Indoor dry location |
| LED type | Top LED |
| Lamp category | LED |
| Number of heads | 1 |
| Power (W) | 8 |
| System power (W) | 18 |
| Source flux (lm) | 754 |
| System flux (lm) | 479 |

Physical

| | |
|-----------------|------------|
| Colour | Matte Rust |
| Orientation | Fixed |
| Net weight (kg) | 0.75 |
| IP | 20 |
| IP external | 20 |

Download

Mounting instructions [↓ PDF](#)


Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F

Schematic light drawing



Beam Angle: 35°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 229 | 2.18 |
| 2 | 57 | 4.36 |
| 3 | 25 | 6.54 |
| 4 | 14 | 8.72 |
| 5 | 9 | 10.90 |

Luminous flux luminaire
479 lm

Photometric

| | |
|------------------------|------------|
| Lighting type | Direct |
| Light distribution | Asymmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| Beam angle C0-180 (°) | 35 |
| Beam angle C90-270 (°) | 46 |

Electrical

| | |
|---------------------------|-----------------|
| Insulation class | III |
| Driver | Remote included |
| Dimmable | Yes |
| Dimming type | Dimmable |
| Emergency type | No |
| Induction recharge Qi | No |
| Charging socket/connector | USB-C |