



## Oblique Qi NEW



Designed by Vincent Van Duysen, 2020



LED - Top LED - 8W - 525lm - 4000K - CRI> 90 - Beam° 35

Oblique is the natural evolution of the classic office swing arm model. With its robust, compact structure and minimalist design, Oblique produces a patented, powerful, and controlled asymmetric light beam that is optimal for workspaces. Key featuresIntegrated USB-C port into the base to charge additional devices. Round flat head for minimal visual intrusion with a 355 rotatable stemA patented ultra-flat lens with very high efficiency of 97%\*Only the Oblique Qi version comes with a built-in wireless charging port at the base. It allows users to charge their smartphones while freeing desks from unsightly wire and cable clutter.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

Mounting	Table
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	8
System power (W)	28
Source flux (lm)	827
System flux (lm)	525

#### **Physical**

Color	Glossy Grey
Orientation	Fixed
IP internal	20
IP external	20



Download	
Family spec sheet	

<u>↓</u> ZIP , PDF

Mounting instructions Mounting instructions

# Photometric Files

LDT / IES

J. ZIP

**₩** PDF

## **Technical Drawings**

2D	<b>↓</b> ZIP
3D	<b>⊥</b> ZIP

https://professional.flos.com/en-US/us/product/oblique-qi-09.8312.ah/

09.8312.AH









### Schematic light drawing



Beam	Angle:	35
h(m)	E(lx)	D(m
1	252	2.18
2	63	4.3
3	28	6.54
4	16	8.72
5	10	10.00

Luminous flux **l**uminaire 525 lm

### Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	46

#### Electrical

Insulation class	III
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable
Emergency type	No
Induction recharge QI	Yes
Charging socket/connector	USB-C