



Perseo 1 NEW




Designed by FLOS Outdoor, 2012



LED source included. Integrated electrical power supply 100-240V ON- OFF. Fixing bracket included. Equipped with a 700 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: ground spike; feet for ground mounting and arms for wall mounting (IP68 connector included). Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793641317
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	7
Source flux (lm)	428
Lumen Output (lm)	401

Physical

Colour	Deep Brown
Orientation	Adjustable
Longitudinal tilting (°)	200
Net weight (kg)	0.61
Package height (mm)	85
Package width (mm)	145
Package length (mm)	235
IP internal	65

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	$\overline{\mathbf{A}}$	ZIP
3D	$\overline{+}$	ZIP













https://professional.flos.com/en/global/product/perseo-1-fa52501318.a/

FA52501318.A

Schematic light drawing



Beam Angle:		8°
h(r	n) E(lx)	D(m)
1	10027	0.13
2	2507	0.27
3	1114	0.40
4	627	0.53
5	401	0.66

30°	7 10	027 d	cd	30°
Lum	inous	flux	lumi	naire
401 I	m			

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	8
Beam angle C90-270 (°)	8
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply





FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



OPTIONAL Accessory

FA15818

Wall Bracket/Pole 600 mm Perseo



OPTIONAL Accessory

FA15718

Wall Bracket/Pole 300 mm Perseo



OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)