

FLOS


FA52505318 Deep Brown

Perseo 2 NEW

Designed by FLOS Outdoor, 2012



LED source included. Integrated electrical power supply 220-240V ON- OFF. Fixing bracket included. Equipped with a 700 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: ground spike; feet for ground mounting and arms for wall mounting (IP68 connector included). Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793642062
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	12
Source flux (lm)	1395
Lumen Output (lm)	828

Physical

Colour	Deep Brown
Orientation	Adjustable
Longitudinal tilting (°)	200
Net weight (kg)	0.97
Package height (mm)	85
Package width (mm)	140
Package length (mm)	235
IP internal	65

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP


Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	42
Beam angle C90-270 (°)	42
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL
Accessory

FA136
Ground Spike Aimer 1/Aimer
2/Aimer 3/Perseo 2



OPTIONAL
Accessory

FA182
Base Plate and Fixing Bolts Perseo
2



OPTIONAL
Accessory

FA17818
Pole with base Perseo 2 h 800
mm



OPTIONAL
Accessory

FA17718
Pole with base Perseo 2 h 500
mm




OPTIONAL
Accessory

FA16218
Wall Bracket/Pole 600 mm Perseo
2



OPTIONAL
Accessory

FA16118
Wall Bracket/Pole 300 mm Perseo
2



OPTIONAL
Accessory

F990E00A000
S.P.D. (SURGE PROTECTION
DEVICE)