



Perseo 2 NEW




Designed by FLOS Outdoor, 2012



LED source included. Integrated electrical power supply 220-240V ON- OFF. Fixing bracket included. Equipped with a 700 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: ground spike; feet for ground mounting and arms for wall mounting (IP68 connector included). Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 



# Main specifications

EAN	8054793646831
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	12
Source flux (lm)	1256
Lumen Output (lm)	866

# Physical

Colour	Black
Orientation	Adjustable
Longitudinal tilting (°)	200
Net weight (kg)	0.97
Package height (mm)	85
Package width (mm)	140
Package length (mm)	235
IP internal	65

## Download

Mounting instructions

₹ ZIP

## Photometric Files

LDT / IES

₹ ZIP

# **Technical Drawings**

2D	$\underline{\bot}$	ZIP
3D	$\overline{\mathbf{T}}$	ZIP

# Schematic light drawing



Bean	n Angle:	13°
h(m)	E(lx)	D(m)
1	8045	0.23
2	2011	0.47
3	894	0.70
4	503	0.94
5	322	1 17

Luminous flux luminaire

#### Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	13
Beam angle C90-270 (°)	13
Extreme cut off	No

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Directorable	
Dimmable	No
Power supply type	Non Dimmable

# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### **Notes**

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

# **Accessories & Power Supply**



OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



OPTIONAL Accessory

FA182

Base Plate and Fixing Bolts Perseo



OPTIONAL Accessory

FA17830

Pole with base Perseo 2 h 800 mm



## OPTIONAL Accessory

FA17730

Pole with base Perseo 2 h 500 mm



## OPTIONAL Accessory

FA16230

Wall Bracket/Pole 600 mm Perseo 2



## OPTIONAL Accessory

FA16130

Wall Bracket/Pole 300 mm Perseo