



Perseo 2 NEW

Designed by FLOS Outdoor, 2012




LED source included. Integrated electrical power supply 220-240V ON- OFF. Fixing bracket included. Equipped with a 700 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: ground spike; feet for ground mounting and arms for wall mounting (IP68 connector included). Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Deen Brown



Main specifications

| EAN | 8054793646886 |
|------------------------|----------------------|
| Mounting | Wall, Ground |
| Environments | Outdoor wet location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| System power (W) | 12 |
| Source flux (lm) | 1256 |
| Lumen Output (lm) | 745 |

Physical

| Colodi | Deep Brown |
|--------------------------|------------|
| Orientation | Adjustable |
| Longitudinal tilting (°) | 200 |
| Net weight (kg) | 0.97 |
| Package height (mm) | 85 |
| Package width (mm) | 140 |
| Package length (mm) | 235 |
| IP internal | 65 |

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

| 2D | $\underline{\boldsymbol{\gamma}}$ | ZIP |
|----|-----------------------------------|-----|
| 3D | $\overline{\mathbf{T}}$ | ZIP |

Schematic light drawing



| Bean | n Angle: | 41° |
|------|----------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1266 | 0.75 |
| 2 | 317 | 1.50 |
| 3 | 141 | 2.25 |
| 4 | 79 | 3.00 |
| 5 | 51 | 3.74 |

Luminous flux luminaire

Photometric

| Light distribution | Symmetric |
|------------------------|-----------|
| CCT (K) | 2700 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 42 |
| Beam angle C90-270 (°) | 42 |
| Extreme cut off | No |

Electrical

| Insulation class | 1 |
|-----------------------------|-------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Power supply | Integrated |
| | |
| Dimmable | No |
| Dimmable Power supply type | No Dimmable |
| | |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990F00A000

S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



OPTIONAL Accessory

FA182

Base Plate and Fixing Bolts Perseo



OPTIONAL Accessory

FA17818

Pole with base Perseo 2 h 800 mm



OPTIONAL Accessory

FA17718

Pole with base Perseo 2 h 500 mm



OPTIONAL Accessory

FA16218

Wall Bracket/Pole 600 mm Perseo 2



OPTIONAL Accessory

FA16118

Wall Bracket/Pole 300 mm Perseo