



Perseo 2 NEW




Designed by FLOS Outdoor, 2012



LED source included. Integrated electrical power supply 220-240V ON- OFF. Fixing bracket included. Equipped with a 700 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: ground spike; feet for ground mounting and arms for wall mounting (IP68 connector included). Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793646893
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	12
Source flux (lm)	1256
Lumen Output (lm)	745

Physical

Colour	Black
Orientation	Adjustable
Longitudinal tilting (°)	200
Net weight (kg)	0.97
Package height (mm)	85
Package width (mm)	140
Package length (mm)	235
IP internal	65

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	↓ ZIP
3D	<u>↓</u> ZIP

Schematic light drawing



Bear	n Angle:	41°
h(m)	E(lx)	D(m)
1	1266	0.75
2	317	1.50
3	141	2.25
4	79	3.00
5	51	3.74

Luminous flux luminaire

Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	42
Beam angle C90-270 (°)	42
Extreme cut off	No

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Dimmable Power supply type	No Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



OPTIONAL Accessory

FA182

Base Plate and Fixing Bolts Perseo 2



OPTIONAL Accessory

FA17830

Pole with base Perseo 2 h 800 mm



OPTIONAL Accessory

FA17730

Pole with base Perseo 2 h 500 mm



OPTIONAL Accessory

FA16230

Wall Bracket/Pole 600 mm Perseo 2



OPTIONAL Accessory

FA16130

Wall Bracket/Pole 300 mm Perseo