

FA52503201 White

Perseo 2 Opal New


Designed by FLOS Outdoor, 2012



LED source included. Integrated electrical power supply 220-240V ON- OFF. Fixing bracket included. Equipped with a 700 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: ground spike; feet for ground mounting and arms for wall mounting (IP68 connector included). Frosted glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793641614
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	11
Source flux (lm)	1258
Lumen Output (lm)	655

Physical

Colour	White
Orientation	Adjustable
Longitudinal tilting (°)	200
Net weight (kg)	0.97
Package height (mm)	85
Package width (mm)	140
Package length (mm)	235
IP internal	65

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D <u>↓</u> ZIP 3D <u>↓</u> ZIP













https://professional.flos.com/en/global/product/perseo-2-opal-fa52503201/

FA52503201

Schematic light drawing



Beam	Angle:	89°
h(m)	E(lx)	D(m)
1	282	1.97
2	70	3.94
3	31	5.91
4	18	7.89
5	11	9.86

Symmetric

4000 80

88

No

Photometric

Beam angle C0-180 (°)

Extreme cut off

Luminous 655 lm	flux	luminaire	

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Power supply type Dimming interface	Non Dimmable Not Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

FA136

Ground Spike Aimer 1/Aimer 2/Aimer 3/Perseo 2



OPTIONAL Accessory

FA182

Base Plate and Fixing Bolts Perseo



OPTIONAL Accessory

FA17801

Pole with base Perseo 2 h 800 mm



OPTIONAL Accessory

FA17701

Pole with base Perseo 2 h 500 mm







OPTIONAL Accessory

FA16201

Wall Bracket/Pole 600 mm Perseo 2

OPTIONAL Accessory

FA16101

Wall Bracket/Pole 300 mm Perseo

OPTIONAL Accessory

990F00A000

S.P.D. (SURGE PROTECTION DEVICE)