

# FLOS

FA52506318-310 Deep Brown


## Perseo 3 Asymmetric Optic Dimmable 1-10V

NEW

Designed by FLOS Outdoor, 2012



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI. Fixing bracket included. Equipped with a M16x1.5 cable guide (for 4.5mm<math>\varnothing</math>10mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: protruding arm for walls; feet and arms to install the luminaire on a mast; wall-washer visor and anti-vandalism protection lid. Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793642536        |
| Mounting               | Wall, Ground         |
| Environments           | Outdoor wet location |
| Light source type      | LED                  |
| Light sources included | Yes                  |
| LED type               | Power LED            |
| Number of lamps        | 1                    |
| System power (W)       | 20                   |
| Source flux (lm)       | 2424                 |
| Lumen Output (lm)      | 1298                 |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | Deep Brown |
| Orientation              | Adjustable |
| Longitudinal tilting (°) | 146        |
| Net weight (kg)          | 2.28       |
| Package height (mm)      | 135        |
| Package width (mm)       | 190        |
| Package length (mm)      | 315        |
| Package volume (m3)      | 0.01       |
| IP internal              | 65         |

### Download

Mounting instructions [Download ZIP](#)

### Photometric Files

LDT / IES [Download ZIP](#)


### Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)



Schematic light drawing



Photometric

|                    |            |
|--------------------|------------|
| Light distribution | Asymmetric |
| CCT (K)            | 3000       |
| CRI>               | 80         |
| Extreme cut off    | No         |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| Power supply       | Integrated        |
| Dimmable           | Yes               |
| Power supply type  | Dimmable 1-10V    |
| Dimming interface  | Dimmer Integrated |
| Emergency          | No                |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL  
Accessory

FA116  
Base Plate and Fixing Bolts for Pole Ø 102 mm h 4000/5000 mm with Base



OPTIONAL  
Accessory

FA16530  
Wall Washer Visor Perseo 3



OPTIONAL  
Accessory

FA182  
Base Plate and Fixing Bolts Perseo 2



OPTIONAL  
Accessory

FA18018  
Pole Inground Perseo 3 h 2000(+300) mm



OPTIONAL  
Accessory

FA17918  
Pole with base Perseo 3 h 800 mm



OPTIONAL  
Accessory

FA16630  
Antivandal Louvre Perseo 3



OPTIONAL  
Bracket

FA22233  
Pole Bracket Franco 1/Perseo 3 Ø 102 mm 180 mm Double



OPTIONAL  
Bracket

FA22206  
Pole Bracket Franco 1/Perseo 3 Ø 102 mm 180 mm Double



OPTIONAL  
Bracket

FA22133

Pole Bracket Franco 1/Perseo 3 Ø  
102 mm 180 mm Single



OPTIONAL  
Bracket

FA22106

Pole Bracket Franco 1/Perseo 3 Ø  
102 mm 180 mm Single



OPTIONAL  
Bracket

FA22406

Pole Bracket Franco 1/Perseo 3 Ø  
102 mm 500 mm Double



OPTIONAL  
Bracket

FA22333

Pole Bracket Franco 1/Perseo 3 Ø  
102 mm 500 mm Single



OPTIONAL  
Bracket

FA22306

Pole Bracket Franco 1/Perseo 3 Ø  
102 mm 500 mm Single



OPTIONAL  
Pole

FA24806

Pole Ø76 mm h 3500 mm(with  
Base)



OPTIONAL  
Pole

FA24833

Pole Ø76 mm h 3500 mm(with  
Base)



OPTIONAL  
Pole

FA25006

Pole Ø76 mm h 3500 mm (+500  
mm In-ground)



OPTIONAL Pole

FA25033  
Pole Ø76 mm h 3500 mm (+500 mm In-ground)



OPTIONAL Pole

FA24906  
Pole Ø76 mm h 4500 mm(with Base)



OPTIONAL Pole

FA24933  
Pole Ø76 mm h 4500 mm(with Base)



OPTIONAL Pole

FA414006  
Pole Ø 102 mm h 4000 mm With Base



OPTIONAL Pole

FA414033  
Pole Ø 102 mm h 4000 mm With Base



OPTIONAL Pole

FA414506  
Pole Ø 102 mm h 4000 mm (+500 mm In-ground)



OPTIONAL Pole

FA414533  
Pole Ø 102 mm h 4000 mm (+500 mm In-ground)



OPTIONAL Pole

FA415006  
Pole Ø 102 mm h 5000 mm With Base



OPTIONAL  
Pole

FA415033

Pole Ø 102 mm h 5000 mm With  
Base



OPTIONAL  
Pole

FA415506

Pole Ø 102 mm h 5000 mm  
(+500 mm In-ground)



OPTIONAL  
Accessory

FA8818

Wall Bracket 620 mm Franco  
1/Perseo 3



OPTIONAL  
Bracket

FA22433

Pole Bracket Franco 1/Perseo 3 Ø  
102 mm 500 mm Double



OPTIONAL  
Bracket

FA22633

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 180 mm Double



OPTIONAL  
Bracket

FA22606

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 180 mm Double



OPTIONAL  
Bracket

FA22533

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 180 mm Single



OPTIONAL  
Bracket

FA22506

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 180 mm Single



OPTIONAL  
Bracket

FA22833

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 500 mm Double



OPTIONAL  
Bracket

FA22806

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 500 mm Double



OPTIONAL  
Bracket

FA22733

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 500 mm Single



OPTIONAL  
Bracket

FA22706

Pole Bracket Franco 1/Perseo 3 Ø  
60 mm 500 mm Single



OPTIONAL  
Bracket

FA23033

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 180 mm Double



OPTIONAL  
Bracket

FA23006

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 180 mm Double



OPTIONAL  
Bracket

FA22933

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 180 mm Single



OPTIONAL  
Bracket

FA22906

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 180 mm Single



OPTIONAL  
Bracket

FA23233

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 500 mm Double



OPTIONAL  
Bracket

FA23206

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 500 mm Double



OPTIONAL  
Bracket

FA23133

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 500 mm Single



OPTIONAL  
Bracket

FA23106

Pole Bracket Franco 1/Perseo 3 Ø  
76 mm 500 mm Single



OPTIONAL  
Pole

FA25106


Pole Ø76 mm h 4500 mm (+500  
mm In-ground)



OPTIONAL  
Pole

FA25133

Pole Ø76 mm h 4500 mm (+500  
mm In-ground)



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)