

FLOS


FA52511306 Grey

Perseo 4 Street Optic NEW

Designed by FLOS Outdoor, 2012



LED source included. Integrated power supply 220-240V ON-OFF and dimmable 1-10V or DALI. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm< $\varnothing$ <13mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: protruding arm for walls; feet and arms to install the luminaire on a mast; wall-washer visor and anti-vandalism protection lid. Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8054793644783
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	53
Source flux (lm)	6363
Lumen Output (lm)	2834

Physical

Colour	Grey
Orientation	Adjustable
Longitudinal tilting (°)	156
Net weight (kg)	5.06
Package height (mm)	155
Package width (mm)	265
Package length (mm)	430
Package volume (m3)	0.02
IP internal	65

Download

[Mounting instructions](#)  ZIP

Photometric Files


[LDT / IES](#)  ZIP

Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP

Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL
Accessory

F990E00A000
S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Pole

FA24806
Pole Ø76 mm h 3500 mm(with
Base)



OPTIONAL
Pole

FA25006
Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA24906
Pole Ø76 mm h 4500 mm(with
Base)



OPTIONAL
Pole

FA25106
Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA414006
Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Pole

FA414506
Pole Ø 102 mm h 4000 mm
(+500 mm In-ground)



OPTIONAL
Pole

FA415006
Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL Pole

FA415506

Pole Ø 102 mm h 5000 mm
(+500 mm In-ground)



OPTIONAL Accessory

FA116

Base Plate and Fixing Bolts for
Pole Ø 102 mm h 4000/5000
mm with Base



OPTIONAL Accessory

FA16730

Wall Washer Visor Perseo 4



OPTIONAL Accessory

FA18106

Wall Bracket Perseo 4 1000 mm



OPTIONAL Accessory

FA16830

Antivandal Louvre Perseo 4



OPTIONAL Bracket

FA9006

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Double



OPTIONAL Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm Double



OPTIONAL Bracket

FA11406

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Double



OPTIONAL
Bracket

FA8906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Double



OPTIONAL
Bracket

FA9606

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Bracket

FA11506

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Double



OPTIONAL
Bracket

FA9306

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm



OPTIONAL
Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm



OPTIONAL
Bracket

FA11206

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Single



OPTIONAL
Bracket

FA11306

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Single



OPTIONAL Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Single