

Perseo 4 Symmetric Optic Dimmable 1-10V

NEW


Designed by FLOS Outdoor, 2012



LED source included. Integrated power supply 220-240V. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm<ø<13mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: protruding arm for walls; feet and arms to install the luminaire on a mast; wall-washer visor and anti-vandalism protection lid. Extraclear transparent glass.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793646381
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	53
Source flux (lm)	6363
Lumen Output (lm)	4332

Physical

Colour	Grey
Orientation	Adjustable
Longitudinal tilting (°)	156
Net weight (kg)	5.06
Package height (mm)	155
Package width (mm)	265
Package length (mm)	430
Package volume (m3)	0.02
IP internal	65

Download

Mounting instructions [ZIP](#)

Photometric Files


LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)

3D [ZIP](#)

Schematic light drawing



Photometric


Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
Extreme cut off	No

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional




Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL
Accessory

F990E00A000
S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Pole

FA24806
Pole Ø76 mm h 3500 mm(with
Base)



OPTIONAL
Pole

FA25006
Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA24906
Pole Ø76 mm h 4500 mm(with
Base)



OPTIONAL
Pole

FA25106
Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA414006
Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Pole

FA414506
Pole Ø 102 mm h 4000 mm
(+500 mm In-ground)



OPTIONAL
Pole

FA415006
Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL Pole

FA415506

Pole Ø 102 mm h 5000 mm
(+500 mm In-ground)



OPTIONAL Accessory

FA116


Base Plate and Fixing Bolts for
Pole Ø 102 mm h 4000/5000
mm with Base



OPTIONAL Accessory

FA16730

Wall Washer Visor Perseo 4



OPTIONAL Accessory

FA18106

Wall Bracket Perseo 4 1000 mm



OPTIONAL Accessory

FA16830

Antivandal Louvre Perseo 4



OPTIONAL Bracket

FA9006

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Double



OPTIONAL Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm Double



OPTIONAL Bracket

FA11406

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Double



OPTIONAL
Bracket

FA8906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Double



OPTIONAL
Bracket

FA9606

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Bracket

FA11506

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Double



OPTIONAL
Bracket

FA9306

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm



OPTIONAL
Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm



OPTIONAL
Bracket

FA11206

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Single



OPTIONAL
Bracket

FA11306

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Single



OPTIONAL Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Single