

FLOS

06.6034.14 Black

Recessed/Surface Feed Connector NEW

Designed by FLOS Architectural, 2020



2m cable included. Electrical connection. Luminaires cannot be located in the connector.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light sources included	No
Power (W)	120

Physical

Colour	Black
Net weight (kg)	0.06



Download

- [Mounting instructions](#) PDF
- [Mounting instructions](#) PDF



Electrical

Insulation class	III
Forward voltage (V)	24
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.

Accessories & Power Supply



OPTIONAL
Power supply

Electrical

60.9681

Remote power supply. Dimmable through 0-1/10V.protocol. 24V. Dimming range 10-100%



OPTIONAL
Power supply

Electrical

60.9683

Remote power supply. Dimmable through Casambi protocol. 24V. Dimming range 10-100%



OPTIONAL
Control interface

Electrical

60.9392

Casambi controller. Requires 1-10V or Dali driver. It must be ordered separately