




Skygarden 1

Designed by Marcel Wanders, Marcel Wanders studio, 2007



Halogen - 150W

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy, liquid-painted white. Molded upper bushing in die-cast, polished aluminum alloy, protected with transparent paint on the entire visible part. Upper cable gland and blocking ring nut in black injection-molded PC (polycarbonate). Shaped, galvanized adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp holder and fixing support in black injection-molded PPS (polyphenylene sulfide). Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Skygarden 1 frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment Gray, injection-molded PA6 (Nylon) rose.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Download Mounting instructions	⊥ PDF	
Photometric Files LDT / IES	⊥ LDT	
Technical Drawings		
_		
2D	₹ ZIP	
_		
2D		

Main specifications

EAN	8059607012772
Mounting	Suspension
Environments	Indoor dry location
Light source type	Bulb
Light sources included	No
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGS
Number of lamps	1
Power (W)	150

Physical

Colour	Gold
Length (mm)	600
Cord colour	Clear
Cord length (mm)	2700
Canopy colour	Gold
Canopy length/diameter (mm)	146
Canopy height (mm)	36
Net weight (kg)	13
Package height (mm)	435
Package width (mm)	730
Package length (mm)	730
Package volume (m3)	0.23
IP internal	20

Schematic light drawing



 Beam Angle:
 118°

 h(m)
 E(lx)
 D(m)

 1
 416
 3.36

 2
 104
 6.72

 3
 46
 10.08

 4
 26
 13.44

 5
 17
 16.79

Photometric


Light distribution	Symmetric
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

https://professional.flos.com/en/global/product/skygarden-1-f0001044/

F0001044




NOT INCLUDED

RF29388

LED T46 Lamp E27 20W 2700K Dimmable

Spare Parts



O1. Gold ceiling rose assembly RF6410144
O2. Skygarden 1 glass diffuser RF6410100
O3. Kit of 5 or rings RF05382





00000

RF6410144

RF6410100

RF05382

Gold ceiling rose assembly

Skygarden 1 glass diffuser

Kit of 5 or rings