

# FLOS

F1367039 Green

## Smithfield Suspension Pro

Designed by Jasper Morrison, 2009



45W - 2791lm - 2700K - CRI > 95

Suspension lamp with direct light. Aluminium body. Available in gloss black, matt black, red, green, white or MUD. Injection-moulded opalescent methacrylate diffuser. Steel ceiling attachment with steel suspension cable, 5 pole electric cable in PTFE double insulation, working length 2700mm.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8059607015001
Mounting	Suspension
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	45
System power (W)	45
System flux (lm)	2791

### Physical

Colour	Green
Length (mm)	600
Cord colour	Clear
Cord length (mm)	2700
Canopy colour	Green
Canopy length/diameter (mm)	146
Canopy height (mm)	36
Net weight (kg)	5.8
Package height (mm)	310
Package width (mm)	710
Package length (mm)	710
Package volume (m3)	0.16
IP internal	20



### Download

[Mounting instructions](#)  PDF

### Photometric Files


[LDT / IES](#)  LDT

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



Luminous flux luminaire  
2623 lm

## Photometric


Light distribution	Roto symmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

## Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Power supply type	Dimmable Push
Batteries inside	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Spare Parts



- |     |  |           |
|-----|--|-----------|
| 01. | Green rose assembly                        | RF1367039 |
| 02. | Kit of 5 or rings                          | RF05382   |
| 03. | 2,7mt fep/pvc 5x0,75 transparent cable     | RF29934   |
| 04. | 3 mt steel cable ø1,2 with 19 winded wires | RF29665   |
| 05. | Driver 60W 500-1400mA 200-240V             | RF31674   |
| 06. | Methacrylate diffuser                      | RF19022   |

RF29934

2,7mt fep/pvc 5x0,75 transparent cable



RF1367039

Green rose assembly

RF05382

Kit of 5 or rings

RF29665

3 mt steel cable  $\varnothing$ 1,2 with 19 wided wires



RF31674

Driver 60W 500-1400mA 200-240V

RF19022

Methacrylate diffuser