

FLOS

F025A4BAU18 Deep Brown

Spine 1 Absolute

Designed by Vincent Van Duysen, 2021




1011lm - 4000K - CRI> 80 - Beam° 15

LED COB light source included. Integrated electric power supply ON/OFF. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately. Upon request: 1-10 V or DALI dimmable version with 24 Vdc remote power supply.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| | |
|------------------------|-----------------------|
| EAN | 8054793419213 |
| Mounting | Ceiling, Wall, Ground |
| Environments | Outdoor wet location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| System power (W) | 11 |
| Source flux (lm) | 1364 |
| System flux (lm) | 1011 |

Physical

| | |
|--------------------------|------------|
| Color | Deep Brown |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 270 |
| Cord length (in) | 196.850 |
| Net weight (lb) | 2.2 |
| Package height (in) | 4.72 |
| Package width (in) | 4.72 |
| Package length (in) | 12.2 |
| Package volume (in) | 272.41 |
| IP internal | 66 |
| IP external | 66 |

Download

| | |
|-----------------------|-----|
| Family spec sheet | ZIP |
| Mounting instructions | ZIP |

Photometric Files

| | |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

Technical Drawings


| | |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Schematic light drawing



Photometric

| | |
|------------------------|-----------|
| Light distribution | Symmetric |
| CCT (K) | 4000 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 15 |
| Beam angle C90-270 (°) | 15 |
| Extreme cut off | No |

Electrical

| | |
|--------------------|--------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 110-127 |
| Driver | Integrated |
| Dimmable | No |
| Dimming type | Non Dimmable |
| Dimming interface | Not Dimmable |

Accessories & Power Supply



OPTIONAL
Accessory

F025Z060000

Honeycomb Louvre



OPTIONAL
Accessory

F026Z010000

Ground Spike