



F026A2BA018 Deep Brown

# **Spine 2 Absolute**

Designed by Vincent Van Duysen, 2021




1939lm - 2700K - CRI> 80 - Beam° 22

LED COB light source included. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

EAN	8054793465043
Mounting	Ceiling, Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
System power (W)	19.5
Source flux (lm)	2197
Lumen Output (lm)	1939

### Physical

Colour	Deep Brown
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Net weight (kg)	1.2
Package height (mm)	120
Package width (mm)	310
Package length (mm)	120
IP internal	66

#### Download

Mounting instructions



#### Photometric Files

LDT / IES



# **Technical Drawings**

2D	<b>↓</b> ZIP
3D	<b>↓</b> ZIP















https://professional.flos.com/en/global/product/spine-2-absolute-f026a2ba018/

F026A2BA018

# Schematic light drawing



Bean	n Angle:	22°
h(m)	E(lx)	D(m)
1	6991	0.38
2	1748	0.77
3	777	1.15
4	437	1.54
5	280	1.92

30 / 07/1 ca / 30 1	3
uminous flux luminaire	
_urninous nux jurninaire	
1939 lm	
1737 [[1]	

# Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	22
Beam angle C90-270 (°)	22

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

### **Accessories & Power Supply**



OPTIONAL Accessory

F026Z010000

Ground Spike



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre