



Spine 2 Pro

Designed by Vincent Van Duysen, 2021




808lm - 3000K - CRI> 80 - Beam° 10

Power LED source included. Equipped with an integrated snoot for higher visual comfort. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

\\/hito



Main specifications

EAN	8054793481203	
Mounting	Ceiling, Wall, Ground	
Environments	Outdoor wet location	
Light source type	rce type LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
System power (W)	tem power (W) 10.5	
Source flux (lm)	966	
Lumen Output (lm)	808	

Physical

Colour	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Net weight (kg)	1.8
Package height (mm)	120
Package width (mm)	310
Package length (mm)	120
IP internal	66

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	$\underline{\bot}$	ZIP
3D	$\overline{\mathbf{T}}$	ZIP
















https://professional.flos.com/en/global/product/spine-2-pro-f026d3ba001/

F026D3BA001

Schematic light drawing



Beam Angle:		9°	
h(r	n) E	(lx)	D(m)
1_	211	05	0.16
2	52	76	0.32
3	23	45	0.48
4	13	19	0.64
5	8	44	0.80

Luminous flux luminaire 808 lm

Photometric

Light distribution	Symmetric	
CCT (K)	3000	
CRI>	80	
Beam angle C0-180 (°)	10	
Beam angle C90-270 (°)	10	

Electrical

Insulation class	1	
Frequency (Hz)	50/60	
Main voltage (Vac)	220-240	
Power supply	Integrated	
Dimmable	No	
Power supply type	Non Dimmable	
Dimming interface	Not Dimmable	
Emergency	No	

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL Accessory

F026Z010000

Ground Spike



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre



OPTIONAL Accessory

F029Z020000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F029Z02100

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F0297022000

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

F0297023000

Converter Spine 2 Optic Elliptic 1



OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall