



F026B2AB012 Forest Green

Spine 2 Ultra Dimmable 1-10V

Designed by Vincent Van Duysen, 2021




230lm - 2700K - CRI> 80 - Beam° 6

Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793468129
Mounting	Ceiling, Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	4.1
Source flux (lm)	248
Lumen Output (lm)	230

Physical

Colour	Forest Green
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Net weight (kg)	1.8
Package height (mm)	120
Package width (mm)	310
Package length (mm)	120
IP internal	66

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D <u>₹</u> ZIP 3D <u>₹</u> ZIP















https://professional.flos.com/en/global/product/spine-2-ultra-dimmable-1-10v-f026b2ab012/

F026B2AB012

Schematic light drawing



Beam Angle:		7°
h(n	n) E(lx)	D(m)
1_	11075	0.12
2	2769	0.23
3	1231	0.35
4	692	0.46
5	443	0.58

Luminous flux luminaire 230 lm

Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	6
Beam angle C90-270 (°)	6

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL Accessory

F029Z020000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F029Z021000

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F029Z02200

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

F029Z02300

Converter Spine 2 Optic Elliptic 1



OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall



OPTIONAL Accessory

F0267050012

Visor



OPTIONAL Accessory

F0267010000

Ground Spike



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre