



F026B2GB030 Black

# Spine 2 Ultra Elliptical 2 Dimmable 1-10V

Designed by Vincent Van Duysen, 2021




699lm - 2700K - CRI> 80

Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

EAN	8054793469362	
Mounting	Ceiling, Wall, Ground	
Environments	Outdoor wet location	
Light source type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
System power (W)	10.5	
Source flux (lm)	920	
Lumen Output (lm)	699	

### **Physical**

Colour	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Net weight (kg)	1.8
Package height (mm)	120
Package width (mm)	310
Package length (mm)	120
IP internal	66

#### Download

Mounting instructions



### Photometric Files

LDT / IES



# **Technical Drawings**

2D ₹ ZIP ₹ ZIP















https://professional.flos.com/en/global/product/spine-2-ultra-elliptical-2-dimmable-1-10v-f026b2gb030/

F026B2GB030

# Schematic light drawing



Bear	n Angle:	24°
h(m)	E(lx)	D(m)
1	1698	0.43
2	424	0.85
3	189	1.28
4	106	1.70
5	68	2.13

Luminous flux luminaire 699 lm

### Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	80

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated
Emergency	No

# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

# **Accessories & Power Supply**



OPTIONAL Accessory

F026Z010000

Ground Spike



### OPTIONAL Accessory

F0267050030

Visor



### OPTIONAL Accessory

F026Z060000

Honeycomb Louvre



### OPTIONAL Accessory

F029Z02000

Converter Spine 2 Optic Medium Flood



### OPTIONAL Accessory

F0297021000

Converter Spine 2 Optic Flood



## OPTIONAL Accessory

F0297022000

Converter Spine 2 Optic Wide Flood



# OPTIONAL Accessory

F0297023000

Converter Spine 2 Optic Elliptic 1



## OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall