



F026C3FA012 Forest Green

Spine 2 Ultra Hp Elliptical 1

Designed by Vincent Van Duysen, 2021




1364lm - 3000K - CRI> 80

Energy-efficient Power LED source included Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| EAN | 8054793476360 | |
|------------------------|-----------------------|--|
| Mounting | Ceiling, Wall, Ground | |
| Environments | Outdoor wet location | |
| Light source type | LED | |
| Light sources included | Yes | |
| LED type | Power LED | |
| Number of lamps | 1 | |
| System power (W) | 17 | |
| Source flux (lm) | 1803 | |
| Lumen Output (lm) | 1364 | |

Physical

| Colour | Forest Green | |
|--------------------------|--------------|--|
| Orientation | Adjustable | |
| Rotation (°) | 360 | |
| Longitudinal tilting (°) | 270 | |
| Net weight (kg) | 1.8 | |
| Package height (mm) | 120 | |
| Package width (mm) | 310 | |
| Package length (mm) | 120 | |
| IP internal | 66 | |

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D ₹ ZIP ₹ ZIP















https://professional.flos.com/en/global/product/spine-2-ultra-hp-elliptical-1-f026c3fa012/

F026C3FA012

Schematic light drawing



| Bear | n Angle: | 14° |
|------|----------|------|
| h(m) | E(lx) | D(m) |
| 1 | 5463 | 0.24 |
| 2 | 1366 | 0.49 |
| 3 | 607 | 0.73 |
| 4 | 341 | 0.98 |
| 5 | 219 | 1.22 |

Luminous flux luminaire 1364 lm

Photometric

| Light distribution | Asymmetric |
|--------------------|------------|
| CCT (K) | 3000 |
| CRI> | 80 |

Electrical

| Insulation class | 1 |
|--------------------|--------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Power supply | Integrated |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming interface | Not Dimmable |
| Emergency | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL Accessory

F0267050012

Visor



OPTIONAL Accessory

F026Z010000

Ground Spike



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre



OPTIONAL Accessory

F029Z02000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F0297021000

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F0297022000

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

F0297023000

Converter Spine 2 Optic Elliptic 1



OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall