



Spine 2 Ultra Hp

Designed by Vincent Van Duysen, 2021




1497lm - 3000K - CRI> 80 - Beam° 15

Energy-efficient Power LED source included Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793474953
Mounting	Ceiling, Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	17
Source flux (lm)	1803
Lumen Outnut (lm)	1497

Physical

Colour	Grey
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Net weight (kg)	1.8
Package height (mm)	120
Package width (mm)	310
Package length (mm)	120
IP internal	66

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	$\underline{\bot}$	ZIP
3D	$\overline{\mathbf{T}}$	ZIP















https://professional.flos.com/en/global/product/spine-2-ultra-hp-f026c3ba006/

F026C3BA006

Schematic light drawing



Ве	am Angle:	15°
h(r	n) E(lx)	D(m)
1_	21400	0.26
2	5350	0.51
3	2378	0.77
4	1337	1.02
5	856	1.28

0°	5	
uminous flux l uminaire		
107 les		

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL Accessory

F029Z020000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F029Z021000

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F029Z02200

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

F029Z02300

Converter Spine 2 Optic Elliptic 1



OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall



OPTIONAL Accessory

F0267050006

Visor



OPTIONAL Accessory

F026Z010000

Ground Spike



OPTIONAL Accessory

F0267060000

Honeycomb Louvre