



F026C3CA033 Anthracite

Spine 2 Ultra Hp

Designed by Vincent Van Duysen, 2021




1386lm - 3000K - CRI> 80 - Beam° 26

Energy-efficient Power LED source included Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793475370	
Mounting	Ceiling, Wall, Ground	
Environments	Outdoor wet location	
Light source type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
System power (W)	17	
Source flux (lm)	1803	
Lumen Output (lm)	1386	

Physical

Colour	Anthracite
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Net weight (kg)	1.8
Package height (mm)	120
Package width (mm)	310
Package length (mm)	120
IP internal	66

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D <u>♣</u> ZIP 3D <u>♣</u> ZIP















https://professional.flos.com/en/global/product/spine-2-ultra-hp-f026c3ca033/

F026C3CA033

Schematic light drawing



Bean	n Angle:	26°
h(m)	E(lx)	D(m)
1	5838	0.47
2	1460	0.93
3	649	1.40
4	365	1.86
5	234	2.33

Luminous flux luminaire 1386 lm

1386 lm

Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	26
Beam angle C90-270 (°)	26

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **E**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL Accessory

F026Z050033

Visor



OPTIONAL Accessory

F0267010000

Ground Spike



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre



OPTIONAL Accessory

F029Z02000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F0297021000

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F0297022000

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

F0297023000

Converter Spine 2 Optic Elliptic 1



OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL Accessory

F029Z025000

Converter Spine 2 Optic Wall