



F025G4BAU18 Deep Brown

Spine F 1 Ultra


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply ON/OFF. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. The rod for ground installations is available in two sizes and needs to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793730837
Mounting	Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
System power (W)	7.9
Source flux (lm)	174
System flux (lm)	149

Physical

Color	Deep Brown
Rotation (°)	360
Longitudinal tilting (°)	270
Cord length (in)	0.197
Net weight (lb)	1.98
Package height (in)	7.48
Package width (in)	9.65
Package length (in)	11.02
Package volume (in)	795.39
IP internal	66
IP external	66

Download

Family spec sheet	↓ ZIP
Mounting instructions	↓ ZIP

Photometric Files

LDT / IES



Technical Drawings

2D	<u>↓</u> ZIP
3D	⊥ ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **E**

https://professional.flos.com/en-US/us/product/spine-f-1-ultra-f025g4bau18/

F025G4BAU18

Schematic light drawing



Beam Angle:		14°
h(m) E(lx)	D(m)
1_	8365	0.24
2	2091	0.48
3	929	0.73
4	523	0.97
	335	1 21

Luminous flux luminaire 591 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80

Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	110-127
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
imming interface Not Dimmable	

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply



REQUIRED Accessory

F026Z020018

Rod Ø20 mm h 200 mm



REQUIRED Accessory

F0267030018

Rod Ø20 mm h 500 mm



OPTIONAL Accessory

F0297010000

Converter Spine 1 Optic Medium Flood



OPTIONAL Accessory

F029Z011000

Converter Spine 1 Optic Flood



OPTIONAL Accessory

F0297012000

Converter Spine 1 Optic Wide Flood



OPTIONAL Accessory

F0297013000

Converter Spine 1 Optic Elliptic 1



OPTIONAL Accessory

F0297014000

Converter Spine 1 Optic Elliptic 2



OPTIONAL Accessory

F0297015000

Converter Spine 1 Optic Wall Washer





OPTIONAL Accessory OPTIONAL Accessory

E0257060000

-0257050018

Honeycomb Louvre

Visor