

# FLOS

 F026G3DBU18 Deep Brown

## Spine F 2 Ultra Dimmable 1-10V


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply ON/OFF and adjustable 1-10 V or DALI. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. The rod for ground installations is available in two sizes and needs to be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793763002        |
| Mounting               | Ground               |
| Environments           | Outdoor wet location |
| Light Source Type      | LED                  |
| Light sources included | Yes                  |
| LED type               | Power LED            |
| System power (W)       | 17                   |
| Source flux (lm)       | 0                    |

### Physical

|                     |            |
|---------------------|------------|
| Color               | Deep Brown |
| Cord length (in)    | 0.197      |
| Net weight (lb)     | 5.51       |
| Package height (in) | 8.07       |
| Package width (in)  | 11.42      |
| Package length (in) | 10.43      |
| Package volume (in) | 958.08     |
| IP external         | 66         |

### Download

|                       |                     |
|-----------------------|---------------------|
| Family spec sheet     | <a href="#">ZIP</a> |
| Mounting instructions | <a href="#">ZIP</a> |

### Photometric Files

|           |                     |
|-----------|---------------------|
| LDT / IES | <a href="#">ZIP</a> |
|-----------|---------------------|

### Technical Drawings


|    |                     |
|----|---------------------|
| 2D | <a href="#">ZIP</a> |
| 3D | <a href="#">ZIP</a> |



### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Schematic light drawing



Photometric

|                    |            |
|--------------------|------------|
| Lighting type      | Direct     |
| Light distribution | Asymmetric |
| CCT (K)            | 3000       |
| CRI>               | 80         |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 110-127           |
| Driver             | Integrated        |
| Dimmable           | Yes               |
| Dimming type       | Dimmable 1-10V    |
| Dimming interface  | Dimmer Integrated |

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply

|                                                                                    |                                                                                    |                                                                                     |                                                                                      |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|   |   |   |   |
| REQUIRED<br>Accessory                                                              | REQUIRED<br>Accessory                                                              | OPTIONAL<br>Accessory                                                               | OPTIONAL<br>Accessory                                                                |
| F026Z020018                                                                        | F026Z030018                                                                        | F026Z050001                                                                         | F026Z060000                                                                          |
| Rod Ø20 mm h 200 mm                                                                | Rod Ø20 mm h 500 mm                                                                | Visor                                                                               | Honeycomb Louvre                                                                     |
|  |  |  |  |
| OPTIONAL<br>Accessory                                                              | OPTIONAL<br>Accessory                                                              | OPTIONAL<br>Accessory                                                               | OPTIONAL<br>Accessory                                                                |
| F029Z020000                                                                        | F029Z021000                                                                        | F029Z022000                                                                         | F029Z023000                                                                          |
| Converter Spine 2 Optic Medium Flood                                               | Converter Spine 2 Optic Flood                                                      | Converter Spine 2 Optic Wide Flood                                                  | Converter Spine 2 Optic Elliptic 1                                                   |



OPTIONAL  
Accessory

F029Z024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL  
Accessory

F029Z025000

Converter Spine 2 Optic Wall