



F026G3DAU30 Black

Spine F 2 Ultra


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply ON/OFF and adjustable 1-10 V or DALI. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. The rod for ground installations is available in two sizes and needs to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793762906
Mounting	Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
System power (W)	17
Source flux (lm)	Λ

Physical

Color	Black
Cord length (in)	0.197
Net weight (lb)	5.51
Package height (in)	8.07
Package width (in)	11.42
Package length (in)	10.43
Package volume (in)	958.08
IP external	66

Download

Download		
Family spec sheet	<u>↓</u> ZIP	
Mounting instructions	↓ ZIP	

Photometric Files

LDT / IES



Technical Drawings

2D	₹ ZIP
3D	₹ ZIP















Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**

https://professional.flos.com/en-US/us/product/spine-f-2-ultra-f026g3dau30/

F026G3DAU30

Schematic light drawing



Beam Angle:		32°
h(m)) E(lx)	D(m)
1_	2101	0.57
2	525	1.15
3	233	1.72
4	131	2.30
5	84	2.87

Luminous flux luminaire 721 lm

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-127
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Dimming interface Not Dimmable	

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply



REQUIRED Accessory

F026Z020030

Rod Ø20 mm h 200 mm



REQUIRED Accessory

F0267030030

Rod Ø20 mm h 500 mm



OPTIONAL Accessory

F026Z050001

Visor



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre



OPTIONAL Accessory

F0297020000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F029Z021000

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F029Z022000

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

E0297023000

Converter Spine 2 Optic Elliptic 1





OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2

OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall