



F025R3GA018 Deep Brown

Spine L 1 Ultra Elliptical 2


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF. Minimum L-shaped mounting support integrated. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Upon request: 1-10 V or DALI dimmable version with 24 Vdc remote power supply.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| EAN | 8054793438351 |
|------------------------|-----------------------|
| Mounting | Ceiling, Wall, Ground |
| Environments | Outdoor wet location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| System power (W) | 7.9 |
| Source flux (lm) | 696 |
| Lumen Output (lm) | 505 |

Physical

| Colour | Deep Brown |
|--------------------------|------------|
| Orientation | Adjustable |
| Longitudinal tilting (°) | 155 |
| Cord length (mm) | 5000 |
| Net weight (kg) | 0.9 |
| Package height (mm) | 190 |
| Package width (mm) | 245 |
| Package length (mm) | 280 |
| Package volume (m3) | 0.01 |
| IP internal | 66 |

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

<u>↓</u> ZIP

Technical Drawings

2D ₹ ZIP ₹ ZIP















https://professional.flos.com/en/global/product/spine-l-1-ultra-elliptical-2-f025r3ga018/

F025R3GA018

Schematic light drawing



| Bean | n Angle: | 26° |
|------|----------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1158 | 0.46 |
| 2 | 290 | 0.91 |
| 3 | 129 | 1.37 |
| 4 | 72 | 1.83 |
| 5 | 46 | 2.28 |

Asymmetric

3000 80

Photometric

| 7 1100 00 1 00 | |
|------------------------|--|
| uminous flux luminaire | |
| 505 lm | |
| | |

Electrical

| Insulation class | 1 |
|-----------------------------|-------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Power supply | Integrated |
| | |
| Dimmable | No |
| Dimmable Power supply type | No Dimmable |
| | |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply





F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F029Z010000

Converter Spine 1 Optic Medium Flood



OPTIONAL Accessory

F029Z011000

Converter Spine 1 Optic Flood



OPTIONAL Accessory

F029Z01200

Converter Spine 1 Optic Wide Flood



OPTIONAL Accessory

F0297013000

Converter Spine 1 Optic Elliptic 1



OPTIONAL Accessory

F0297014000


Converter Spine 1 Optic Elliptic 2



OPTIONAL Accessory

F0297015000

Converter Spine 1 Optic Wall Washer



OPTIONAL Accessory

F990C100000

Gelbox IPX8 for splicing connectors







OPTIONAL Accessory

F0257060000

Honeycomb Louvre

OPTIONAL Accessory

F0257050018

\/icor

OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)