



F025R3AA012 Forest Green

Spine L 1 Ultra

Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF. Minimum L-shaped mounting support integrated. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Upon request: 1-10 V or DALI dimmable version with 24 Vdc remote power supply.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793437989
Mounting	Ceiling, Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	3.5
Source flux (lm)	174
Lumen Output (lm)	149

Physical

Colour	Forest Green
Orientation	Adjustable
Longitudinal tilting (°)	155
Cord length (mm)	5000
Net weight (kg)	0.9
Package height (mm)	190
Package width (mm)	245
Package length (mm)	280
Package volume (m3)	0.01
IP internal	66

Download

Mounting instructions

₹ ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D <u>♣</u> ZIP 3D <u>♣</u> ZIP















https://professional.flos.com/en/global/product/spine-l-1-ultra-f025r3aa012/

F025R3AA012

Schematic light drawing



Beam Angle:		7
h(m)) E(l×)	D(r
1	5888	0.1
2	1472	0.2
3	654	0.3
4	368	0.4
5	236	0.6

Symmetric

3000 80

8

Photometric

Beam angle C0-180 (°)

Beam angle C90-270

uminous flux	uminaire
49 lm	

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply





F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F990C100000

Gelbox IPX8 for splicing connectors



OPTIONAL Accessory

F025Z060000

Honeycomb Louvre



OPTIONAL Accessory

F025Z05001

Visor



OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F0297010000

Converter Spine 1 Optic Medium Flood



OPTIONAL Accessory

F0297011000

Converter Spine 1 Optic Flood



OPTIONAL Accessory

F0297012000

Converter Spine 1 Optic Wide Flood



OPTIONAL Accessory

F0297013000

Converter Spine 1 Optic Elliptic 1



OPTIONAL Accessory

F0297014000

Converter Spine 1 Optic Elliptic 2



OPTIONAL Accessory

F029Z015000

Converter Spine 1 Optic Wall Washer