

# FLOS

F026V3AD001 White

## Spine L 2 Pro Dimmable Dali


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Minimum L-shaped mounting support integrated. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                       |
|------------------------|-----------------------|
| EAN                    | 8054793521367         |
| Mounting               | Ceiling, Wall, Ground |
| Environments           | Outdoor wet location  |
| Light source type      | LED                   |
| Light sources included | Yes                   |
| LED type               | Power LED             |
| Number of lamps        | 1                     |
| System power (W)       | 4.1                   |
| Source flux (lm)       | 258                   |
| Lumen Output (lm)      | 239                   |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | White      |
| Orientation              | Adjustable |
| Longitudinal tilting (°) | 155        |
| Net weight (kg)          | 2.5        |
| Package height (mm)      | 205        |
| Package width (mm)       | 290        |
| Package length (mm)      | 265        |
| Package volume (m3)      | 0.02       |
| IP internal              | 66         |

### Download

Mounting instructions [ZIP](#)

### Photometric Files

LDT / IES [ZIP](#)


### Technical Drawings

2D [ZIP](#)

3D [ZIP](#)



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 6         |
| Beam angle C90-270 (°) | 6         |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| Power supply       | Integrated        |
| Dimmable           | Yes               |
| Power supply type  | Dimmable DALI 1   |
| Dimming interface  | Dimmer Integrated |
| Emergency          | No                |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E


Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply

|                                                                                    |                                                                                    |                                                                                     |                                                                                      |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|   |   |   |   |
| OPTIONAL<br>Accessory                                                              | OPTIONAL<br>Accessory                                                              | OPTIONAL<br>Accessory                                                               | OPTIONAL<br>Accessory                                                                |
| F990C030000                                                                        | F990C080000                                                                        | F990C110000                                                                         | F026Z060000                                                                          |
| 4 way junction box 5 poles IP68<br>(6-14 mm cables)                                | Connector kit 5-pole flying socket<br>+ EU plug IP68.                              | Gelbox IPX8 for splicing<br>connectors                                              | Honeycomb Louvre                                                                     |
|  |  |  |  |
| OPTIONAL<br>Accessory                                                              | OPTIONAL<br>Accessory                                                              | OPTIONAL<br>Accessory                                                               | OPTIONAL<br>Accessory                                                                |
| F029Z020000                                                                        | F029Z021000                                                                        | F029Z022000                                                                         | F029Z023000                                                                          |
| Converter Spine 2 Optic Medium<br>Flood                                            | Converter Spine 2 Optic Flood                                                      | Converter Spine 2 Optic Wide<br>Flood                                               | Converter Spine 2 Optic Elliptic 1                                                   |



OPTIONAL  
Accessory

F029Z024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL  
Accessory

F029Z025000

Converter Spine 2 Optic Wall