



F026V3BA033 Anthracite

Spine L 2 Pro


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Minimum L-shaped mounting support integrated. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

| EAN | 8054793521473 |
|------------------------|-----------------------|
| Mounting | Ceiling, Wall, Ground |
| Environments | Outdoor wet location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| System power (W) | 10.5 |
| Source flux (lm) | 966 |
| Lumen Output (lm) | 808 |

Physical

| Colour | Anthracite |
|--------------------------|------------|
| Orientation | Adjustable |
| Longitudinal tilting (°) | 155 |
| Net weight (kg) | 2.5 |
| Package height (mm) | 205 |
| Package width (mm) | 290 |
| Package length (mm) | 265 |
| Package volume (m3) | 0.02 |
| IP internal | 66 |

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

| 2D | $\underline{\bot}$ | ZIP |
|----|-------------------------|-----|
| 3D | $\overline{\mathbf{T}}$ | ZIP |















https://professional.flos.com/en/global/product/spine-l-2-pro-f026v3ba033/

F026V3BA033

Schematic light drawing



| Ве | am Angl | e: 9° |
|-----|--------------|--------|
| h(r | n) E(lx |) D(m) |
| 1 | 21105 | 0.16 |
| 2 | 527 <i>6</i> | 0.32 |
| 3 | 2345 | 5 0.48 |
| 4 | 1319 | 9 0.64 |
| 5 | 844 | 1 0.80 |

| 30° | 721 | 105 a | :d\ | 30° |
|-------|-------|-------|------|-------|
| Lum | inous | flux | lumi | naire |
| 808 l | m | | | |

Photometric

| Light distribution | Symmetric |
|------------------------|-----------|
| CCT (K) | 3000 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 10 |
| Beam angle C90-270 (°) | 10 |

Electrical

| Insulation class | 1 |
|----------------------------|--------------|
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Power supply | Integrated |
| | |
| Dimmable | No |
| Dimmable Power supply type | Non Dimmable |
| | |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.


Accessories & Power Supply



OPTIONAL Accessory

F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F990C11000C

Gelbox IPX8 for splicing connectors



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre



OPTIONAL Accessory

F990C01000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F029Z020000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F029Z021000

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F029Z022000

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

F029Z023000

Converter Spine 2 Optic Elliptic 1





OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2

OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall