



F026V3HA030 Black

# Spine L 2 Pro Wall Washer


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Minimum L-shaped mounting support integrated. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use.

Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 



## Main specifications

EAN	8054793522548
Mounting	Ceiling, Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	10.5
Source flux (lm)	966
Lumen Output (lm)	698

## **Physical**

Colour	Black
Orientation	Adjustable
Longitudinal tilting (°)	155
Net weight (kg)	2.5
Package height (mm)	205
Package width (mm)	290
Package length (mm)	265
Package volume (m3)	0.02
IP internal	66

## Download

Mounting instructions

<u>↓</u> ZIP

### Photometric Files

LDT / IES

₹ ZIP

# **Technical Drawings**

₹ ZIP ₹ ZIP















https://professional.flos.com/en/global/product/spine-I-2-pro-wall-washer-f026v3ha030/

F026V3HA030

# Schematic light drawing



Bean	n Angle:	10°
h(m)	E(lx)	D(m)
1	3689	0.18
2	922	0.37
3	410	0.55
4	231	0.73
5	148	0.92

Luminous flux luminaire

# Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	80

### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Dimmable Power supply type	No Non Dimmable

# Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **E** 



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

### **Notes**

5 m neoprene cable (10 m upon request) for remote connection.


### **Accessories & Power Supply**



OPTIONAL Accessory

F990C00A000

2 way terminal block 4 poles IP68 H20 stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

F990C110000

Gelbox IPX8 for splicing connectors



### OPTIONAL Accessory

F026Z06000

Honeycomb Louvre



### OPTIONAL Accessory

F990C01000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



### OPTIONAL Accessory

F029Z020000

Converter Spine 2 Optic Medium Flood



### OPTIONAL Accessory

F029Z021000

Converter Spine 2 Optic Flood



### OPTIONAL Accessory

F029Z022000

Converter Spine 2 Optic Wide Flood



### OPTIONAL Accessory

F029Z023000

Converter Spine 2 Optic Elliptic 1





OPTIONAL Accessory

F029Z024000

FUZ9ZUZ4UUU

Converter Spine 2 Optic Elliptic 2

OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall