

FLOS

■ F02504BAU30 Black

Spine T 1 Absolute


Designed by Vincent Van Duysen, 2021



LED COB light source integrated. Integrated electric power supply ON/OFF. Integrated support for pole fixing, for poles with a diameter between 60 and 120 mm and a maximum thickness of 3 mm. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Upon request: 1-10 V or DALI dimmable version with 24 Vdc remote power supply.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793411200
Mounting	Pole Top
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
System power (W)	11
Source flux (lm)	1364
System flux (lm)	1011

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Cord length (in)	196.850
Net weight (lb)	1.98
Package height (in)	10.43
Package width (in)	11.42
Package length (in)	8.07
Package volume (in)	961.37
IP internal	66
IP external	66

Download

Family spec sheet	ZIP
Mounting instructions	ZIP

Photometric Files

LDT / IES	ZIP
-----------	-----

Technical Drawings


2D	ZIP
3D	ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-127
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Dimming interface	Not Dimmable

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply



OPTIONAL
Accessory

FA116
Base Plate and Fixing Bolts for
Pole Ø 102 mm h 4000/5000
mm with Base



OPTIONAL
Accessory

F025Z060000
Honeycomb Louvre



OPTIONAL
Accessory

F990G300000
Base plate with Bolts for Pole Ø
76 mm h 3000/4000 mm with
Base