



F02513GAU18 Deep Brown

Spine T 1 Ultra Elliptical 2


Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply ON/OFF. Integrated support for pole fixing, for poles with a diameter between 60 and 120 mm and a maximum thickness of 3 mm. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793737850	
Mounting	Pole Top, Wall, Ground, Floor	
Environments	Outdoor wet location	
Light Source Type	LED	
Light sources included	Yes	
LED type	Power LED	
System power (W)	7.9	
Source flux (lm)	rce flux (Im) 174	
System flux (lm)	149	

Physical

Color	Deep Brown
Rotation (°)	360
Longitudinal tilting (°)	270
Cord length (in)	196.850
Net weight (lb)	1.98
Package height (in)	10.43
Package width (in)	11.42
Package length (in)	8.07
Package volume (in)	961.37
IP internal	66
IP external	66

Download

-amily spec sheet	$\overline{\gamma}$	ZIP
Mounting instructions	$\overline{\mathbf{A}}$	ZIP

Photometric Files

LDT / IES



Technical Drawings

2D	↓ ZIP
3D	⊥ ZIP













https://professional.flos.com/en-US/us/product/spine-t-1-ultra-elliptical-2-f02513gau18/

F02513GAU18

Schematic light drawing



Bean	n Angle:	26°
h(m)	E(lx)	D(m)
1	1158	0.46
2	290	0.91
3	129	1.37
4	72	1.83
5	46	2.28

Luminous flux luminaire

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-127
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Dimming interface	Not Dimmable

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply





F029Z010000

Converter Spine 1 Optic Medium Flood



OPTIONAL Accessory

F029Z011000

Converter Spine 1 Optic Flood



OPTIONAL Accessory

F029Z012000

Converter Spine 1 Optic Wide Flood



OPTIONAL Accessory

F029Z01300

Converter Spine 1 Optic Elliptic 1



OPTIONAL Accessory

F0297014000

Converter Spine 1 Optic Elliptic 2



OPTIONAL Accessory

F0297015000

Converter Spine 1 Optic Wall Washer



OPTIONAL Accessory

F0257060000

Honeycomb Louvre



OPTIONAL Accessory

F0257050018

Visor