



F02613CBU18 Deep Brown

Spine T 2 Ultra Dimmable 1-10V

Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply ON/OFF and adjustable 1-10 V or DALI. Integrated support for pole fixing, for poles with a diameter between 60 and 120 mm and a maximum thickness of 3 mm. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8054793774145	
Mounting	Pole Top	
Environments	Outdoor wet location	
Light Source Type	LED	
Light sources included	Yes	
LED type	Power LED	
System power (W)	17	
Source flux (lm)	0	

Physical

Color	Deep Brown	
Rotation (°)	360	
Longitudinal tilting (°)	270	
Cord length (in)	0.197	
Net weight (lb)	5.51	
Package height (in)	8.07	
Package width (in)	10.43	
Package length (in)	11.42	
Package volume (in)	961.37	
IP external	66	



Download

Family spec sheet	↓ ZIP
Mounting instructions	<u>↓</u> ZIP

Photometric Files

LDT / IES



Technical Drawings

2D	⊥ ZIP
3D	⊥ ZIP

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **F**













IK 09

https://professional.flos.com/en-US/us/product/spine-t-2-ultra-dimmable-1-10v-f02613cbu18/

F02613CBU18

Schematic light drawing



Beam Angle:		27°
h(m)	E(lx)	D(m)
1	3076	0.48
2	769	0.97
3	342	1.45
4	192	1.93
5	123	2.41

Luminous flux luminaire 742 lm

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80

Electrical

Insulation class	1	
Frequency (Hz)	50/60	
Main voltage (Vac)	110-127	
Driver	Integrated	
Dimmable	Yes	
Dimming type	Dimmable 1-10V	
Dimming interface Dimmer Integrate		

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply





F026Z050018

Visor



OPTIONAL Accessory

F026Z060000

Honeycomb Louvre



OPTIONAL Accessory

F029Z020000

Converter Spine 2 Optic Medium Flood



OPTIONAL Accessory

F029Z02100

Converter Spine 2 Optic Flood



OPTIONAL Accessory

F029702200

Converter Spine 2 Optic Wide Flood



OPTIONAL Accessory

F0297023000

Converter Spine 2 Optic Elliptic 1



OPTIONAL Accessory

F0297024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL Accessory

F0297025000

Converter Spine 2 Optic Wall